



46 40 24mm



51mm 42mm 28mm



172mm 82mm 36mm

1 产品概述

DT-7141HE

2 主要特性

- ❖ HDMI
- ❖ DR-2108A 1080P 300MHz-860MHz 1W
- 5-10 3W 7-20
- 860MHz-2400MHz 500mW , 1-3
- ❖ 280~320MS
- ❖ 1W 12W 3W 20W
- ❖ 105
- ❖ H.264
- ❖
- ❖
- ❖ USB
- ❖ DC12V/DC24V DC 10V-26V
- ❖
- ❖



230Km/h

3 技术指标

	300~2400MHz, 10 KHz
	300MHz-860MHz≤3W 860MHz-2400MHz≤500mW 5W 10W
	COFDM DVB-T
	2M 4M 6M 7M 8M
	1-8Mbps
	1/2,2/3,3/4,5/6,7/8
	1/32,1/16,1/8,1/4
	QPSK,16QAM,64QAM
	2K 8K
	≤25dB
	1920 1080_60P,1920 1080_50P 1920 1080_60i,1920 1080_50i 1280 720_60P,1280 720_50P 720 576_50i,720 480_60i
	MPEG-4 AVC/H.264
	0.8Mbps~30Mbps
	CBR
	IPPP
	MPEG-1 Layer2
	48KHz
	24-bit
	64Kbps-192Kbps
	280~320MS
	RPSMA MMCX 50
	HDMI
	RF RPSMA
	DC 24V/DC 12V
	-10 ~50 (

	-20 ~75 ()		
	PAL/NTSC		
	300MHz-860MHz,1W	5-10	3W 7-20
	860MHz-2400MHz,1-3		
	≤105		
		46 40	24mm
		51 42	28mm

	100MHz-932MHz	
	COFDM DVB-T	
	75Ω	
	HDMI CVBS	
	-95.8dBm	
	6M/7M/8M	
	QPSK, 16QAM, 64QAM	
	1/32, 1/16, 1/8, 1/4	
	1/2, 2/3, 3/4, 5/6, 7/8	
	2K 4K 8K	
	MPEG-4 AVC /H.264 HP@L4 MPEG-2 MP @HL/ML	
	4:3/16:9	
	PAL/NTSC	
	1±0.3Vpp	
	HDMI	1920 1080_30P,1920 1080_25P 1920 1080_60i,1920 1080_50i 1280 720_60P,1280 720_50P 720 576_50i,720 480_60i
	CVBS	720 576_50i 720 480_60i
	MPEG-2/HE_AAC(DD/DD+)	
	+	
	1 RCA	2 RCA
	USB	
	≤10W	
	DC+12V~24V±10%	
	-10 ~+50	
	214g	
	172mm 82mm 36mm	

4 原理框图

